

ADJUSTABLE WASH TOOL

Company
Services
CT Completions
CT Surface
CT Sub-Surface
CT Service Tools
Wellheads
Slickline
Engineering Data
Index



Description

The Adjustable Wash Tool is run on the bottom of the coiled tubing string. The Wash Tool has a threaded connection and can be run with a variety of connections, check valves or other equipment. The tool can be adjusted to many different spray configurations for depth washing, de-scaling, perforation clean up, chemical washes or debris clean-out. By simply turning the adjustable body, the cleaning fluids can be directed in a fanning method or angled as required; thus, there is no need to have multiple nozzles in inventory.

Applications

- Well-cleaning operations.

Features & Benefits

- Threaded connection makes up to a variety of connectors.
- Can be run with check valves or other equipment.
- Manufactured from hardened steel for long life.
- Adjustable spray provides an effective clean-out.
- Simple design consists of only two manufactured parts.
- Easy field service.

Specifications

Coiled Tubing Sizes (in. / mm)	Tool OD (in. / mm)	Tool ID (in. / mm)	Connections	Temp. Rating (°F / °C)	PSI (MPa)
0.75 - 1.75 (19.05 - 44.45)	1.6875 (42.86) 2.125 (53.97)	0.93 (23.62) 1.25 (31.75)	Available in various threads to suit customer requirements	-40 - 275 (-40 - 135)	2000 (14)
2 (50.80)	2.125 (53.97)	1.25 (31.75)			
2.375 - 2.875 (60.32 - 73.02)	2.5 (63.5)	1.5 (38.10)			