

VERTICAL ACCESS DUAL STRING HANGER



Description

The Vertical Access Dual String Hanger permits the installation of larger-coiled tubing strings in the well. By design, the tubing strings remain near-vertical for easy access.

Applications

- Used with single or dual-coiled tubing strings for multi-zone completions, chemical injection, velocity strings, clean-out operations and wireline access.

Features & Benefits

- Vertical access to both primary and secondary strings allows passage of wireline tools.
- Integral union for simplified installation, compatible with Select hydraulic annular control valve.
- Standard 2" line pipe side port eliminates the need for an additional flow tee sub; thus reducing costs and wellhead height.
- One-piece machined alloy steel body.
- The unique swivel nut retention system of the upper valve assemblies ensures a leak-free connection when aligning to the surface flowline(s).
- Larger-coiled tubing sizes available upon request.

Specifications

Coiled Tubing Sizes		Casing Sizes (in. / mm)	Union (in. / mm)	PSI (MPa)
Min. (in. / mm)	Max. (in. / mm)			
1 (25.40)	1.75 (44.45)	4.5 (114.30)	4 (101.60) Fig. 206 Male Sub and Nut	2000 (14)
1.25 (31.75)	2 (50.80)	5.5 (139.70)	5 (127.00) Fig. 400 Male Sub and Nut	2500 (17)

Company
Services
CT Completions
CT Surface
CT Sub-Surface
CT Service Tools
Wellheads
Slickline
Engineering Data
Index